

- ✓ Digital Display for LEL
- ✓ Audible Tick Rate
- ✓ Preset Alarms

- ✓ 0 to 2000 ppm CO Readings✓ Calculate and Display CO Air Free
- ✓ UL 913 Certification

SENSIT® GOLD EXCO+1200 can also be used as an OSHA-compliant confined space monitor.

As an investigative tool, the LEL sensor is designed to find the source of combustible gas leaks fast.

Applications

- Combustible Gas Leak Detection
- Carbon Monoxide Investigations
- Confined Space Monitoring
- Combustible Gas Measurements
- BPI 1200 Energy Audits

You can depend on the **SENSIT® GOLD EXCO+1200** to provide the safety and accuracy you need.

Displays 3 Gases

- LEL (Combustibles)
- Oxygen
- Carbon Monoxide (PPM)
- Air Free CO Readings (CF)

Standard Features

- UI 913 Certified
- Audible Tick Leak Detection
- · Lowest Cost, Long Life Sensors
- Internal Pump
- Water/Dust Filter
- Field Calibration
- Calibration Alert
- Session Log
- Calibration Memory
- Infrared Download
- Audible/Visual Alarms
- Bright LCD Display
- Programmable Auto Shut Off

SENSIT® GOLD EXCO+1200

PRODUCT FEATURES

- LUER PROBE CONNECTOR
- SENSOR CAP
- LEL / PPM SENSOR
- INFRARED COMMUNICATIONS
- 5 BACKLIT LCD DISPLAY

- ALARM LEDS
- **OPERATION BUTTONS**
- TICK ADIUST
- FLEXIBLE GOOSENECK
- 10 BATTERY COMPARTMENT

PRODUCT SPECIFICATIONS

Size: 11.5" x 3" x 2.32" (29.2 x 7.6 x 6.9 cm)

1.2 lb. (0.5 kg) Weight:

-4 to 122 F (-20 to 50° C) Operational Temp:

Battery Life: Alkaline: Approximately 12 hrs. Continuous







TYPE RESOLUTION LEAK (UL) N/A

0.1% up to 2.0% LEL

0.1% O_2 CO 1 ppm **RANGE**

10-50,000 ppm 0-100% LEL ±10%

0-25% ±0.2% or 10%** 0-2000 ppm ±5 ppm or 5%**

N/A

**Whichever is greater

ACCURACY



MADE IN USA

SENSIT Technologies is in compliance with ISO 9001:2008









Distributed by:

InspectorTools[™]

SENSIT"GOLD

InspectorTools.com 4848 Colt Street Suite 11

Ventura CA 93003

(800) 895-4916 (805) 644-4316

Fax: (805) 644-5362

Email: moreinfo@inspectortools.com